



# ULTRA 624 M

with Cradle Device

● MADE  
● IN  
● GERMANY

# SETEC

## ULTRA 624 M

### TECHNICAL DETAILS

Total width	Table width + 850 mmg
Total width with platform	Table width + 1000 mmg
Working width	Table width - 200 mmg
Maximum roll diameter	450 mmg
Maximum lay height	180 mmg
Maximum machine speed	ca. 100m/ming
Maximum roll weight	80 kg
Machine weight	ca. 240 kg
Power supply	220/380 V; 50 Hzg



**-optional-  
Cloth roll bar device**

Spreading several rolls at the same time. Up to 3 axis connectable. Field of application for example: spreading neckties with 45° cut.



**-optional-  
Spreadingdevice for tubu-  
lator fabric**

Is equipped with detachable platform and calander.  
- optional - folding to the middle



**-optional-  
Cradle device**

Two powerful motors upwind your fabric synchronised.

**setec**

## STANDARD EQUIPMENT

- Short ply programm
- Ply programming with ply packages with constant length
- Sequential threading
- Prism driven top carriage
- Metric control with storage linear dimension and position calculator
- Fabric feeding roll with electrical synchronization and tip-operator
- Dragging roll with integrated threading automatics
- Safety sensors on user and non-user-side
- Input of total number of ply and bundle
- Micro processing controlled with screen and keyboard
- Electronic controlled soft start
- Safety squeeze and sheer position
- Elevator controll by photocell scanning
- No wearing parts, feeding roll is driven electrically
- Transistor protection of short circuit for the complete motors and all electrical exits

low-maintenance

processreliable

productive

efficient



**Cloth Roll Hoist**

Simple setting the spreading machine even with heavy rolls with the Setec Hoister 120.



**Operation Display**

LCD screen with self explaining menu, working with contrast and lightning regulation. Diagnostic service through service stuff - Service menu: All functions are testable (motors, cards...)



**Cutting**

The cutting device is featured by a long life time and after consumption even a novice can change the unit within 20 seconds.



**Twist Grip**

Swiss quality potentiometer guarantees up to  $6 \cdot 10^7$  turns.

**setec**

## References from customers all over the world:



Betty Barclay



**ROLF  
BENZ**



**BOSS**  
HUGO BOSS



**JIL SANDER**




**EvoBus**

### SETEC Maschinenbau GmbH

Robert-Bosch-Str. 9  
72525 Münsingen

Telefon: +49 7381 189-0  
Fax: +49 7381 189-44  
E-Mail: [info@setec-info.de](mailto:info@setec-info.de)



[www.setec-info.de](http://www.setec-info.de)